

MICHELIN ROADBIB



***THE SOLUTION
FOR HEAVY
ROAD USE***

FOR HIGH POWERED
TRACTORS*

* Tractors of at least 160 hp



MICHELIN

MICHELIN ROADBIB

Tire specifications and pressure table (bar & psi). Load per tire in kg

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)	
30	ROADBIB 540/65R30 150D/146E TL	NEW	274757	547	1464	679	4382	DW16L	W18L	754	332	32.5

Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	1930	2185	2445	2700	3000	3300	3600	3900	4200	4405	4615	4820	5025
30 km/h	1480	1755	2030	2310	2585	2860	3135	3315	3495	3675	3855		
40 km/h		1695	1955	2210	2470	2725	2985	3155	3330	3500	3670		
50 km/h		1630	1875	2120	2370	2615	2860	3025	3190	3355	3520		
65 km/h			1800	2030	2265	2495	2725	2880	3040	3195	3350		
70 km/h			1640	1850	2060	2270	2480	2610	2740	2870	3000		

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)	
30	ROADBIB 600/70R30 158D/154E TL		264539	592	1617	726	4800	DW20B(A)	DW18L DW21B(A)	192 251	468	42.0


Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2510	3015	3515	4020	4520	5160	5795	5930	6065	6265	6460	6770	7075
30 km/h	1925	2325	2725	3125	3525	3925	4325	4480	4640	4795	4950		
40 km/h		2200	2565	2935	3300	3670	4035	4205	4375	4545	4715		
50 km/h		2110	2460	2815	3165	3515	3865	4030	4195	4355	4520		
65 km/h			2360	2680	3000	3325	3650	3800	3950	4100	4250		
70 km/h			2150	2440	2730	3025	3320	3430	3535	3645	3750		

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)	
34	ROADBIB 650/60R34 159D/155E TL	NEW	556249	667	1651	762	4935	DW20B (A)	DW21B (A) DW23B (A)	823	500	38.5

Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2475	2800	3125	3450	3885	4320	4755	5190	5625	5860	6095	6330	6565
30 km/h	1900	2285	2665	3050	3435	3815	4200	4410	4615	4825	5030		
40 km/h		2190	2550	2910	3275	3635	3995	4195	4395	4590	4790		
50 km/h		2100	2445	2795	3140	3490	3835	4025	4215	4405	4595		
65 km/h			2300	2640	2975	3310	3650	3830	4015	4195	4375		
70 km/h			2095	2400	2710	3015	3320	3460	3600	3735	3875		

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)	
34	ROADBIB 650/65R34 161D/157E TL	NEW	330378	674	1707	785	5098	DW20B (A)	DW21B (A) DW23B (A)	823	555	39.5

Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2700	3090	3475	3865	4290	4720	5145	5575	6000	6235	6470	6705	6940
30 km/h	2070	2470	2865	3265	3660	4055	4455	4670	4890	5105	5320		
40 km/h		2385	2755	3130	3500	3875	4245	4450	4655	4860	5065		
50 km/h		2290	2645	3000	3360	3715	4070	4265	4465	4660	4855		
65 km/h			2575	2900	3225	3550	3875	4065	4250	4440	4625		
70 km/h			2345	2640	2935	3230	3525	3675	3825	3975	4125		





Tire specifications and pressure table (bar & psi). Load per tire in kg

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)			
42	ROADBIB 650/65R42 165D/161E TL	075643	633	1932	870	5733	DW20B (A)	DW23B (A) DW21B(A)	802	643	43.2			
Bar (Psi)		0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h		3000	3400	3800	4200	4675	5145	5620	6090	6565	6855	7145	7435	7725
30 km/h		2300	2730	3165	3595	4025	4460	4890	5150	5410	5665	5925		
40 km/h			2660	3060	3460	3855	4255	4655	4900	5150	5395	5640		
50 km/h			2550	2935	3315	3700	4080	4465	4700	4940	5175	5410		
65 km/h				2800	3165	3525	3890	4250	4475	4700	4925	5150		
70 km/h				2550	2880	3210	3540	3870	4060	4250	4435	4625		

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)			
42	ROADBIB 710/70R42 173D/179E TL	749845	720	2076	938	6177	DW23B(A)	DW25B(A)	170 006	867	38.5			
Bar (Psi)		0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h		3750	4275	4800	5325	6000	6675	7350	8025	8700	8965	9225	9490	9750
30 km/h		2875	3470	4065	4660	5255	5845	6440	6700	6960	7215	7475		
40 km/h			3285	3855	4425	4995	5560	6130	6380	6625	6875	7120		
50 km/h			3150	3695	4240	4785	5335	5880	6120	6355	6590	6825		
65 km/h				3550	4065	4575	5090	5600	5825	6050	6275	6500		
70 km/h				3230	3700	4165	4630	5095	5270	5450	5625	5800		

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)			
42	ROADBIB 710/75R42 175D/171E TL	378080	742	2143	964	6368	DW23B (A)	DW25B (A) DW21B(A)	802	950	43			
Bar (Psi)		0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.80 (26)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h		3975	4525	5075	5625	6300	6975	7650	8325	9000	9340	9675	10015	10350
30 km/h		3050	3690	4335	4975	5615	6260	6900	7160	7420	7675	7935		
40 km/h			3560	4160	4765	5365	5970	6570	6815	7065	7310	7555		
50 km/h			3415	3990	4570	5145	5725	6300	6535	6775	7010	7245		
65 km/h				3750	4315	4875	5440	6000	6225	6450	6675	6900		
70 km/h				3415	3925	4440	4950	5460	5635	5805	5980	6150		

IMPORTANT:

The inflation pressure is always determined according to the load per tire, speed and work to be carried out and according to the legislation in force in the country.
30, 40, 50, 65 and 70 km/h: use on the road up to 30, 40, 50, 65 and 70 km/h.

MICHELIN ROADBIB



EXTRAORDINARY PERFORMANCE IN TERMS OF LONGEVITY

- Exclusive design: new tread pattern
- Directional tires

GREAT COMFORT

- Smooth central rib improves comfort on roads
- Reduced space between patterns (compared to traditional sculptures) limits cabin vibrations
- Quiet running tire - outdoors and indoors

+5% FUEL SAVINGS*

- A wide footprint combined with an optimized tread depth provides
- Low rolling resistance and thus reduced fuel consumption

* versus Premium competitive tire with classic lugs (650/65 R42 & 540/65 R30). Fuel consumption test carried out in June 2020 - Ladoux/France



LONG-LASTING TIRE



FUEL SAVINGS



COMFORT

SIZES

NEW 540/65R30 150D/146E TL

NEW 650/65R34 161D/157E TL

NEW 710/75R42 175D/171E TL

600/70R30 158D/154E TL

NEW 650/65R42 165D/161E TL

NEW 650/60R34 159D/155E TL

710/70R42 173D/179E TL

MICHELIN ADVICE

VEHICLE N° 1

FRONT PRESSURE (bars / psi)

REAR PRESSURE (bars / psi)

VEHICLE N° 2

FRONT PRESSURE (bars / psi)

REAR PRESSURE (bars / psi)



agro.michelin.com



MICHELIN