



KIVI-PEKKA 3,3 STONE PICKER

Kivi-Pekka 3.3 stone picker is the latest addition to the Kivi-Pekka rock picker family. In addition to traditional cultivation, the machine is developed for special cultivation and landscaping. Kivi-Pekka 3.3 is a very efficient machine in its size group. It is agile to operate, transport and maintain.

Huge capacity with 2 meter (6,5') wide lifting drum and 5 m³ (6,5 yd³) large stone hopper

The machine has a lifting drum up to 2 meters (6,5') wide, from which the stones are picked inside the machine. On the sides of the lifting drum are simple s-spike rotors that guide the stones to the center of the machine. The lifting drum uses Kivi-Pekka's strong tines, which take in stones up to 35 centimeters (13,7") in diameter. The working width of the machine is 3.3 meters. The stone tank has a large volume of 5 cubic meters (6,5 yd³). The machine is able to collect 900 kilograms (2000 lbs) of stones per minute.

The power requirement of the machine is modest. As its drawbar weight is less than 1000 kg (2200 lbs), a tractor with 60 horsepower with a single-acting hydraulic output is sufficient to pull Kivi-Pekka 3.3. Thanks to drawbar mounting the machine will turn agilely in narrow places. The drawbars also ensures an accurate working depth.

The tipping height is 210 centimeters (78"), so the stones can be easily tipped on a truck. The machine needs only one hydraulic block for tipping. The low and sturdy structure of the machine ensures safe tipping even on an uneven ground.

The Kivi-Pekka 3.3 hopper has a same kind of soil box as in larger models of Kivi-Pekka. Soil box ensures that the stones are cleaned during the tipping phase and the soil ends up in the field.



KIVI-PEKKA 3,3 TECHNICAL DATA

Weight 3490 kg (7700 lbs)
Working width 330 cm (10.8 ft)
Transport width 299 cm (118 in)
Stone size 2,5-35 cm Ø (1-13,7 in)
Output 900 kg/min (2000 lbs/min)
Stone hopper volume 5 m³ (6,5 yd³)
Tyre size 380(15 in)/85×24
Power requirement 60 hp
Hydraulics 20 l/min (5.3 gal/min)
Running speed 1-6 km/h (0,6-3,7 mph)
Lifting drum tines 53 pcs
Tipping height 210 cm (78 in)



QUALITY FROM FINLAND

The durability of the machine has been achieved as a result of progressive product development over the past 35 years. The right materials and the best components keep running costs low.



www.pel-tuote.fi

PEL-Tuote Oy

Seppälänsalmentie 181
FIN-58900 Rantasalmi
FINLAND

EXPORT

Mikko Lappalainen
mikko.lappalainen@pel-tuote.fi
mob: +358 40 550 8115